

WELDING POSITIONER

Will hold 795 kgs in the horizontal position and 454 kgs in the vertical position
 Note: C/G of load not be more than 150 mm from the centre of the turntable and 150 mm from the face of the turntable.

Technical Specifications

| | |
|---------------------------------|-----------------|
| Capacity Vertical: | 454 kg |
| Capacity Horizontal: | 795 kg |
| Load Center of Gravity: | 152 mm |
| Tilt: | Power |
| Tilt Angle (Degrees): | 0 - 135 |
| Tilt Angle Indicator: | N/A |
| Ground Capacity: | 500 Amps |
| Grounding Device: | Brass |
| High Freq. Protection: | Yes |
| Volt/Ac: | 115 or 230 |
| Power Req. 115V: | 10 Amp |
| Table Thickness: | 25 mm |
| Table Diameter: | 612 mm |
| Table Configuration: | 3 & 4 - Slot |
| Optional Chucks: | WPC-12, 16 & 20 |
| Optional Grippers: | WPG-22 & 26 |
| Table Height (Horizontal): | 855 mm |
| Table Center Height (Vertical): | 736 mm |
| Through Hole: | N/A |
| Table R.P.M: | 0.2 - 2 |
| Rotation Motor H.P: | 1/4 H.P. |
| Variable Speed Rotation: | on panel |
| Foot Control: | Fwd./Rev. |
| Hand Pendant: | Optional |
| Anchor Points: | 6 |
| Levelling Bolts: | Included |
| Unit Width: | 819 mm |
| Unit Length: | 1231 mm |
| Shipping Weight (Approx.): | 546 kgs |



Features

- 612.5 mm Diameter Table
- 0.2 to 2 rpm Rotation Speed
- Power Tilt Adjustment
- 230 Volt
- 0 - 135° Tilting Angle
- High Frequency Protected
- Standard Fwd/Rev. Foot Control with 12' (3.6 m) cord
- Shipping Weight 546 kgs
- 1 Year warranty

| Part Number | Includes |
|-------------|--------------------------|
| WP1000-2 | Machine and Foot Control |