

WELDING POSITIONER

Will hold 4318 kgs in the horizontal position and 2727 kgs in the vertical position
 Note: C/G of load not be more than 304 mm from the centre of the turntable and 304 mm from the face of the turntable.

Technical Specifications

Capacity Vertical:	2727 kg
Capacity Horizontal:	4318 kg
Load Center of Gravity:	304 mm
Tilt:	Power
Tilt Angle (Degrees):	0 - 135
Tilt Angle Indicator:	Standard
Ground Capacity:	800 Amps
Grounding Device:	Rotary
High Freq. Protection:	Yes
Volt/AC:	220 or 440 (3 PH.)
Power Req. 115V:	10 Amp
Table Thickness:	25 mm
Table Diameter:	1200 mm
Table Configuration:	3 & 4 - Slot
Optional Chucks:	WPC-20 & 25
Optional Grippers:	WPG-22, 26 & 34
Table Height (Horizontal):	1092 mm
Table Center Height (Vertical):	927 mm
Through Hole:	N/A
Table R.P.M:	0.1 - 1.2
Rotation Motor H.P:	2 H.P.
Variable Speed Rotation:	on pendant
Foot Control:	Opt.
Hand Pendant:	Standard
Anchor Points:	6
Levelling Bolts:	Included
Unit Width:	1200 mm
Unit Length:	1800 mm
Shipping Weight (Approx.):	1239 kgs



Features

- 1200 mm Diameter table
- 0.1 to 1.2 rpm Rotation speed
- 440 Volt 3 phase
- 0 - 135° Tilting angle
- High frequency protected
- Standard hand control pendant
- Shipping weight 1239 kgs
- 1 Year warranty

Part Number	Includes
WP6000-4	Machine and Foot Control

* Note: Primary input cable and plug not supplied