



## WELDING POSITIONER

Designed for rotation of lighter pieces.  
 Will hold 200 kgs in the horizontal position  
 and 113 kgs in the vertical position  
 Note: C/G of load not to be more than 100  
 mm from the centre of the turntable and 100  
 mm from the face of the turntable

### Technical Specifications

Capacity Vertical:	113 kg
Capacity Horizontal:	200 kg
Load Center of Gravity:	101 mm
Tilt:	Manual
Tilt Angle (Degrees):	0 - 90
Tilt Angle Indicator:	N/A
Ground Capacity:	300 Amps
Grounding Device:	Brass
High Freq. Protection:	Yes
Volt/Ac:	115 or 230
Power Req. 115V:	5 Amp
Table Thickness:	14 mm
Table Diameter:	340 mm
Table Configuration:	3 - Slot
Optional Chucks:	WPC-6 & 11
Optional Grippers:	-
Table Height (Horizontal):	335 mm
Table Center Height (Vertical):	255 mm
Through Hole:	28 mm
Table R.P.M:	0 - 5.5
Rotation Motor H.P:	1/8 H.P.
Variable Speed Rotation:	on panel
Foot Control:	Single
Hand Pendant:	Optional
Anchor Points:	4
Levelling Bolts:	N/A
Unit Width:	313 mm
Unit Length:	525 mm
Shipping Weight (Approx.):	52 kgs



### Features

- 340 mm Diameter Table
- 0 to 5.5 rpm Rotation Speed
- Manual Tilt Adjustment
- 240 Volt
- 0 -90° Tilting Angle
- High Frequency Protected
- Standard with Foot Control 12' cord (3.6 m)
- Shipping Weight 51 kgs
- 1 Year warranty

Part Number	Includes
WP250-2	Machine and Foot Control